

# EVERLAST LOOPS PREFORMED INDUCTIVE LOOP <u>MODEL P16</u> (POLYPROPYLENE LOOP HEAD)

Description: Model P16 detection loops are designed for installation into concrete pour, asphalt overlays, and direct burial. This model provides cost-effective, reliable installation in harsh environments. Model P16 has the flexibility to withstand the rigors of the installation process.

LOOP HEAD	LEAD-IN	TEE	WIRE	O.D.
POLYPROPYLENE	HYDRAULIC FLEX	SCHEDULE	14 AWG STR	5/8 INCH
PIPING	HOSE	80 CPVC	THHN/THWN-2	(16MM)

#### APPLICATION

Concrete Pour (with or without rebar) / Hot Asphalt overlay / Direct Burial (dirt & gravel)

## CONDUIT

Loop Head conduit: Thermoplastic Polypropylene pipe(PP)

• Lead-In conduit: PVC/Polyurethane hydraulic hose (polyurethane alloy cover tube, high tensile strength yarn reinforcement, polyurethane alloy cover)

- Excellent cut, abrasion, and impact resistance
- Superior resistance to moisture, salt, gasoline, and oil (Class A)
- Great flexibility over wide temperature range
- 5/8 inch O.D. (16 millimeter) / 3/8 inch I.D (9.5 millimeter)

## CONNECTION

- Schedule 80 CPVC tee to join loop head and lead-in (wire passes through -- no splices within tee)
- Strongest tee available Dimensions: 3 inch long (1-1/8 inch O.D.)

#### WIRE

- Loop wire is 14 gauge AWG thhn/tffn stranded(19), single conductor with PVC installation and nylon exterior jacket
- One continuous wire through the loop head and lead-in to prevent loop malfunctions due to splicing
- Wires within lead-in are machine twisted at 6 twists per foot

## **CONSTRUCTION NOTES**

• The entire loop (loop head, tee, lead-in) shall be filled with hot rubberized self sealing emulsion which allows the loop to remain flexible once cooled, prevent incursion of moisture, and set the wire firmly in place.

- Loop heads feature expansion/contraction joints at intervals to allow pavement movement.
- Loops shall be tested four ways prior to shipment ("megger", inductance, ohms, quality-factor).
- All loops factory produced and come with a full 15 year manufacturer's warranty.

EVERLAST LOOPS MODEL P16 (2020)

Everlast Loops LLC Milwaukie, OR, USA Tel: ++1 503-869-1631 Email: info@everlastloops.com Internet: <u>www.everlastloops.com</u>

